

# PA-8525

NEW



The One-of-a-kind Highly Integrated Fanless 15" POS Terminal



## Features

- Intel® Celeron® J1900 CPU
- 15" LCD display with Bezel Free Touch Screen
- Flexible design for versatile applications
- Optional 2"/3" easy loading thermal printer
- Optional MSR, i-Button & Fingerprint & RFID
- Small footprint and Streamline design
- It can be rotated 180° to operate with stand




## Specifications


System	CPU Support	Intel® Celeron® J1900 CPU
	Memory	DDR3L SO-DIMM (1 slot, up to 8GB)
	Network	10/100/1000 Base-T Fast Ethernet
	Power Supply	72~120Watt Power Adapter
	Audio	2W Speaker
	System Weight	with power adaptor approx. 6kg
	Dimension	378 X 380 X 168mm
	O.S. Support	WIN8 / POSReady7
Storage	SATA	1 x 2.5" HDD or SSD
	USB	3 x USB on rear, 1 x USB on side bezel
	Serial Port	3 x DB9 (+5V/ 12V selectable)
	LAN	1 x RJ45
	VGA	1 x DB15
	Line Out	1 x phone jack
	Cash Drawer	1 + 1(option, with Y cable) x RJ11 (+12V or +24V selectable)
	DC-in	1 x 4pin DC Power Jack
Peripheral	Customer Display	VFD kit, 20 columns and 2 lines, each column is 5 x 7 dots
	Printer	2" or 3" easy loading thermal printer with Auto cutter
	MSR & iButton	ISO I,II,III; JIS I,II and support information key
	RFID	ISO14443A Read /Write; ISO18092 Read only
	Fingerprint	8-bit grayscale, reader
Display	LCD	15" TFT LCD
	Max. Resolution	1024x768
	Brightness	250 cd/m <sup>2</sup>
	Touch Screen	5-wire Analog resistive
	Tilt Angle	29 ~ 50 degrees
Environment	EMC & Safety	CE / FCC
	Operating Temp.	0 ~ 35° C
	Storage Temp.	-5 ~ 60° C
	Humidity	20 ~ 90%

\*All information contained in this document is subject to change without prior notice. Please log on [www.protech.com.tw](http://www.protech.com.tw) to acquire latest information

## Highlights



## System I/O Ports






## Ordering Information

Order No	Description
PA-8525RC-A0B	PA-8525 barebone, Intel® Celeron® J1900 15" POS /black /1024x768 LED Backlight , Resistance TouchScreen
PA-3122RZ-21A	DDR3L 2GB memory/ 2.5" HDD
PA-8525RZ-91A	Embedded MSR, PS2 interface
PA-8225RZ-51B	Embedded VFD module, RS232 interface
PA-8225RZ-42B	Embedded 3" Thermal Printer, USB interface
52-002-02012001	120 Watt Power Adaptor

## Applications

- Hospitality
- Retail
- Replacement of ECR

## Dimensions



unit: mm

### Protech Systems Co., Ltd.

No. 24, Lane 365, Yang Goang Street,  
Nei Hu District Taipei 114, Taiwan R.O.C.  
TEL: +886-2-8751-1111

### Protech Technologies Inc.

950 Fee Ana St, Suite B  
Placentia, CA 92870  
TEL: +1-714- 996-7200

### Protech Japan Co., Ltd.

OSK Bldg, 6F, 6-25-14, Minami-ohi  
Shinagawa-ku, Tokyo, 140-0013  
TEL: +81-3-5753-8411

### PROX SYSTEMS Germany GmbH

Weststrasse 20a, 40721 Hilden  
düsseldorf, Germany  
TEL: +49 (0) 2103-41898-18